



E-Star Power Development Co., Ltd. (E-STAR)  
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City  
 22069, Taiwan (R.O.C.)  
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

**60~65W Travel Power Supply < PA1060-IB**

## FEATURES

**Over-Voltage Protection**  
**Over-Current Protection**

**Limit current Protection(Optional)**

**Short-circuit Protection**  
**100%Hi-pot & ATE(Chroma)Tested**

**100%Burn-in under High**  
**Ambient Temperature(45℃)**

**Low Ripple/Noise**  
**MTBF Above 50000 HRS At 25℃**

**LVD authentication**  
**Limited Power Sources(LPS)**

**CEC IV and V Efficiency**  
**Regulations Compliance**

**Cispr 22 CLASS B,VCCI CLASS B,**  
**FCC Part15 CLASS B, Compliance**

# PA1060 IB Series

## Interchangeable 2PIN Type



## SPECIFICATION

Model No	PA1060-2IB	PA1060-3IB	PA1060-4IB	PA1060-5IB
Part No	PA1060-120IB~ PA1060-149IB	PA1060-150IB~ PA1060-240IB	PA1060-241IB~ PA1060-360IB	PA1060-361IB~ PA1060-480IB
Item				
<b>Output Voltage</b>	12~14.9V	15~24V	24.1~36V	36.1~48V
<b>Output Current(Max.)</b>	5.0A	4.33A	2.69A	1.8A
<b>Output Power(Max.)</b>	60W	65W	65W	65W
<b>Input Voltage</b>	AC90~264V			
<b>Input Frequency</b>	47~63Hz			
<b>Input Current</b>	1.8A Maximum			
<b>Inrush Current</b>	80A Maximum			
<b>Line Regulation</b>	1% Maximum			
<b>Ripple&amp;Noise</b>	1% Maximum			
<b>Load Regulation</b>	5% Maximum			
<b>Efficiency</b>	≥ 87%			
<b>Operating Temperature</b>	0~40℃			
<b>Storage Temperature</b>	-20~85℃			
<b>Over-Voltage Protection</b>	Auto Recovery			
<b>Short-circuit Protection</b>	Auto Recovery			
<b>Safety Standard</b>	CB,CCC,UL,BSMI,PSE,TUV-GS,CEC			
<b>EMC(EMI/EMS)</b>	CE,FCC,C-Tick,VCCI,LVD,LPS			



E-Star Power Development Co., Ltd. (E-STAR)

1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City  
22069, Taiwan (R.O.C.)

Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

**60~65W Travel Power Supply < PA1060-IB**

## 機種編碼 Products code:

PA 1 060 - XXX I B XXX - XXX - XX

