



E-Star Power Development Co., Ltd. (E-STAR)  
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City  
 22069, Taiwan (R.O.C.)  
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

## 60W Travel Power Supply < PA1060

### Features

Over-Voltage Protection  
 Over-Current Protection

Limit current Protection(Optional)

Short-circuit Protection  
 100%Hi-pot & ATE Tested

100%Burn-in under (45°C)

Low Ripple/Noise  
 MTBF 50000 HRS At 25°C

LVD authentication  
 Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency  
 Regulations Compliance

Cispr 22 CLASS B, VCCI CLASS B,  
 FCC Part15 CLASS B, Compliance

### PA1040/50/60 Series Wall Mount -2Prong Interchangeable Plug-In



### Specification

Model No Transformer	PA1040-xyzPA1050-xyzPA1060-xyz														
	ER28-1 or PQ2620-1	ER28-2 or PQ2620-2		ER28-2 or PQ2620-2		ER28-3 or or PQ2620-2			ER28-4 or PQ2620-3			ER28-5 or PQ2620-4			
Output Voltage	5.0~8.9V	9~14.9V	9~11.9V	12~14.9V		15~24V			24.1~36V			36.1~57V			
Type(PA1040/50/60)	PA1040	PA1040	PA1050	*50	*60	*40	*50	*60	*40	*50	*60	*40	*50	*60	
Output Current(Max.)	7.0A	4.44A	5A	4.17A	5A	2.66A	3.33A	4A	1.66A	2.07A	2.48A	1.10A	1.38A	1.66A	
Output Power(Max.)	35W	40W	45W	50W	60W	40W	50W	60W	40W	50W	60W	40W	50W	60W	
Input Voltage	AC90~264V														
Input Frequency	47~63Hz														
Input Current	1.5A Max														
Inrush Current	60A Max														
Line Regulation	1% Max														
Ripple&Noise	1% Max														
Load Regulation	5% Max														
Efficiency	DoE VI & CoC Teir 2 VI														
Operating Temperature	0~40°C														
Storage Temperature	-20~85°C														
Over-Voltage Protection	Auto Recovery														
Short-circuit Protection	Auto Recovery														
Safety Standard	CB, UL, cUL, TUV-GS, LVD, UKraine, Kvalitet, BSMI, PSE, NOM, SAA, RCM, MEPS, DoE, CCC														
EMC(EM/EMS)	CE, FCC, VCCI, RCM														

