



E-Star Power Development Co., Ltd. (E-STAR)
 1F., No.40, Juren Ln., Sec. 2, Sanmin Rd., Banciao Dist., New Taipei City
 22069, Taiwan (R.O.C.)
 Phone : 886-2-2957 5580 Fax : 886-2-2957 7473

53 ~ 65W Travel Power Supply < PA1065

Features

Over-Voltage Protection
 Over-Current Protection

Limit current Protection(Optional)

Short-circuit Protection
 100%Hi-pot & ATE Tested

100%Burn-in under(45°C)

Low Ripple/Noise
 MTBF 50000 HRS At 25°C

LVD authentication
 Limited Power Sources(LPS)

DoE VI and CoC Tier 2 VI Efficiency
 Regulations Compliance

Cispr 22 CLASS B,VCCI CLASS B,
 FCC Part15 CLASS B, Compliance

PA1065 Series Wall Mount-2Prong Interchangeable Plug-In



Specification

Model No	PA1065-xxxxyyzzz			
Transformer	POT30-1	POT30-2	POT30-3 or RM-10	POT30-4
Output Voltage	5~8.9V	9~14.9V	15~24V	24.1~57V
Output Current(Max.)	8A	6A	4.33A	2.7A
Output Power(Max.)	53W	65W	65W	65W
Input Voltage	AC 90~264V			
Input Frequency	47~63Hz			
Input Current	1.5A Max			
Inrush Current	80A Max			
Line Regulation	1% Max			
Ripple& Noise	1% Max			
Load Regulation	5% Max			
Efficiency	DoE VI & CoC Tier 2 VI			
Operating Temperature	0~40°C			
Storage Temperature	-20~85°C			
Over-Voltage Protection	Auto Recovery			
Short-circuit Protection	Auto Recovery			
Safety Standard	CB,UL,cUL,cTUVus,TUV-GS,LVD,SAA,RCM,PSE,ST,Nrcan,ERP,MEPS,DoE			
EMC (EM/EMS)	CE,FCC,VCCI,RCM			

